



BSR Series

Borehole Servicing Rigs

Built on the same tough principles as its drilling rigs, Dando's BSR borehole servicing rigs offer a range of features to enable the development, servicing and remediation of water wells.



Dando BSR Series

Specifications

	BSR10	BSR16	BSR24
Carrier Vehicle	6 x 6 heavy duty truck	6 x 6 heavy duty truck	6 x 6 heavy duty truck
Power Unit	80 hp diesel engine	101 hp diesel engine	126 hp diesel engine
Mast Hook Load	10000 kgf	16000 kgf	24000 kgf
Mast Working Height	9140 mm	9140 mm	11500 mm
Service Winch Hoist (Single line, bare drum)	3700 kg	8000 kg	8000 kg
Winch Speed (Single line, bare drum)	27 m/min	42 m/min	35 m/min
Winch Drum Capacity	83m @ 12 mm	121m @ 18mm	129m @ 18mm
Controls	Hydraulic power circuit based on load sensing, proportional valves. Drilling controls available from driller's control console		
Levelling Jacks	2 x front ; 2 x rear		
Lighting	Fitted as standard		

Optional Equipment

Hydraulic Freefall Winch	3000 kg capacity hydraulic freefall winch for bailing and fishing tasks
Jetting Pump	Selection of duplex and triplex piston pumps for jetting operations
Airlifting Compressor	Selection of compressors available from 400cfm/200psi to 1070cfm/350psi
Welders/Generators	Selection of welders/generators available
Generators	Selection of generators available
Mast Layback	1m - 1.5m laybacks available

Please note: All figures and claims made here are indicative and Dando Drilling International reserves the right to make alterations to specification detail without notice. All images are for reference only and may not represent the exact specification outlined in this document.